

**SIEMENS**



[siemens.com/sitransLR250](https://www.siemens.com/sitransLR250)

## Hygienic applications? Meet your approved liquids level solution

Say hello to level measurement for tracking inventory. For production of food or beverages. Or use in the life sciences. With the sanitary approvals and long-term performance stability that you need.

Welcome to liquid level measurement perfection: introducing SITRANS LR250 radar transmitter with a fully encapsulated antenna and FDA-approved USP Class VI TFM 1600 PTFE lens material.

Simple installation using industry-standard process connections, non-contacting reliability, ease of use: see what SITRANS LR250 can do for you.



**Answers for industry.**

# SITRANS LR250 – your radar solution for liquids and slurries

SITRANS LR250 is your choice for liquid level measurement in storage and process vessels. With its new encapsulated antenna, hygienic applications are no problem for this transmitter. Reliability and improved safety? We have that. A class-leading range of process connections? That too. Welcome to liquid level perfection.

So, what do you need from your level measurement instrument? We're guessing it's exactly what SITRANS LR250 has to offer.

## Simple installation

Easily installed on a variety of locations, with smaller process connections – as small as 2" (50 mm). 25 GHz frequency ensures reliable readings even with obstructions in your vessel.

And did we mention the graphical HMI? Making operation simple with plug-and-play setup using the intuitive Quick Start Wizard.

## Minimal maintenance

The flush-mounted lens antenna is easy to clean and reduces buildup – no need to remove during clean-in-place (CIP) cycles. Plus, the transmitter is suitable for temperatures up to 170 °C (338 °F).

## Approved for use

With EHEDG (EL Class 1 and EL Class 1 Aseptic) and 3-A certification as well as FDA and USP Class VI-approved materials, SITRANS LR250 is ideal for your hygienic, sanitary, or aseptic applications.

## True inventory management

Understanding exactly what your storage or process vessel contains means no shutdowns or slowdowns in production – only the highest in product quality and consistency.

## Reliable echo profiles

Process Intelligence signal processing for improved measurement reliability and Auto False-Echo Suppression of fixed obstructions.

## Flexible communications

Whatever your communications preference, we've got it: HART, PROFIBUS PA, FOUNDATION Fieldbus.



## SITRANS LR250 family features

- **Application flexibility** – from sanitary processes to harsh environments, choose from horn, PVDF, or encapsulated antenna designs
- **Easy to install** – small antennas and narrow beams allow installation practically anywhere on your vessel
- **Quick to configure** – Quick Start Wizard for simple setup
- **Process Intelligence** – advanced echo processing for unparalleled performance
- **Reliable and accurate** – extremely high signal and low noise yields high performance, even with low dielectric media. Plus SIL 2 for applications requiring functional safety





<b>SITRANS LR250 Hygienic Encapsulated Antenna</b>	
<b>Order No.</b>	7ML5433
	2-wire, 25 GHz pulse radar level transmitter for continuous monitoring of liquids and slurries in storage and process vessels including hygienic/sanitary environments in the food, beverage, pharmaceutical and fine chemical industries
<b>Range</b>	20 m (66 ft)
<b>Process temperature</b>	-40 to 170 °C (-40 to 338 °F)
<b>Process pressure</b>	Up to 16 bar g (580 psi g), process connection dependent
<b>Key features</b>	<ul style="list-style-type: none"> <li>• Process Intelligence – advanced echo processing for unparalleled performance</li> <li>• Graphical HMI (Human-Machine Interface)</li> <li>• Quick Start Wizard and display diagnostics</li> <li>• Complies with IEC 61508/61511 standard for functional safety (SIL 2)</li> <li>• 3-A, EHEDG EL Class 1 and EL Class 1 aseptic certification with TFM 1600 PTFE-wetted antenna parts (FDA and USP Class VI approved) for hygienic and sanitary environments</li> <li>• SITRANS LR250 hygienic variations:               <ul style="list-style-type: none"> <li>• Sanitary Clamp according to ISO 2852</li> <li>• Aseptic/Hygienic nozzle/ slotted nut (instrument side) to DIN 11864-1 [Form A]</li> <li>• Aseptic/Hygienic flanged to DIN 11864-2 [Form A]</li> <li>• Aseptic/Hygienic Clamp according to DIN 11864-3 [Form A]</li> <li>• Hygienic nozzle/ slotted nut (instrument side) to DIN 11851</li> <li>• Tuchenhagen Varivent Type F</li> <li>• Tuchenhagen Varivent Type N</li> </ul> </li> </ul>
<b>Communications and outputs</b>	<ul style="list-style-type: none"> <li>• HART, PROFIBUS PA, or FOUNDATION Fieldbus</li> <li>• Enhanced EDD for SIMATIC PDM, Emerson AMS, SITRANS DTM (for PACTware), 375/475 handheld, for configuration and diagnostics</li> </ul>

Find out more:  
[siemens.com/sitransLR250](http://siemens.com/sitransLR250)

SITRANS LR250 –  
discover all that your  
liquids level solution  
has to offer: visit us  
online to see for  
yourself.



Subject to change without prior notice  
Printed in Canada  
© Siemens AG 2014

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.

All product designations may be trademarks or product names of Siemens AG or supplier companies whose use by third parties for their own purposes could violate the rights of the owners.

Follow us on:  
[twitter.com/siemensensors](https://twitter.com/siemensensors)  
[youtube.com/thinksiemens](https://youtube.com/thinksiemens)  
[facebook.com/siemensensors](https://facebook.com/siemensensors)

Siemens AG  
Industry Sector  
Sensors and Communication  
76181 KARLSRUHE  
GERMANY