

SIMATIC S7-300, DIGITAL OUTPUT SM 322, OPTICALLY ISOLATED 16 DO, 120/230V AC, 1 A, 1 X 20 PIN



Figure similar

Supply voltage	
Load voltage L1	
• Rated value (AC)	230 V; 120/230V AC
• permissible range, lower limit (AC)	79 V
• permissible range, upper limit (AC)	264 V
Input current	
from load voltage L1 (without load), max.	2 mA
from backplane bus 5 V DC, max.	200 mA
Power loss	
Power loss, typ.	8.6 W
Digital outputs	
Number of digital outputs	16
Switching capacity of the outputs	
• on lamp load, max.	50 W
Output current	
• for signal "1" rated value	1 A
• for signal "1" minimum load current	10 mA

• for signal "1" permissible surge current, max.	20 A; with 2 half waves
• for signal "0" residual current, max.	2 mA
Switching frequency	
• with resistive load, max.	10 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	1 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 40 °C, max.	4 A
— up to 60 °C, max.	2 A
vertical installation	
— up to 40 °C, max.	2 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	No
Diagnostic messages	
• Diagnostic functions	Yes; Fuse blown or load voltage missing
• Wire-break	No
• Short-circuit	No
• Fuse blown	Yes
• missing load voltage	No
Diagnostics indication LED	
• Rated load voltage PWR (green)	No
• Fuse OK FSG (green)	Yes; Red LED for fuse
• Group error SF (red)	Yes
• Status indicator digital output (green)	Yes
Potential separation	
Potential separation digital outputs	
• between the channels, in groups of	8
• between the channels and backplane bus	Yes; Optocoupler
Isolation	
Isolation tested with	4000 VDC
Connection method	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm

Depth	120 mm
Weights	
Weight, approx.	275 g
last modified:	12.09.2015