



THE BRITELUX™ LAMP SERIES is 25% brighter than conventional 130 volt lamps. They produce a crisp bright light that is comparable to krypton lamps. They are ideal for residential applications and available in a wide variety of shapes and wattages.

A19



A21



B10



BR30



BR40



G16.5



G25



G30



G40



R20



S11



Order code	Description	Watts (W)	Base	Volts (V)	Finish/Colour	Average life (hrs)	Filament	Initial lumens (lm)	MOL (in.) (mm)	LCL (in.) (mm)	Case qty
A19											
50920	25A19/CL/1M/120V/STD BLX/2P (2 pack)	25	E26	120	Clear	1000	C-9	230	4.3 108	2.9 73	120
50931	25A19/CL/1M/120V/STD BLX/4P (4 pack)	25	E26	120	Clear	1000	C-9	215	4.3 108	2.9 73	120
50932	25A19/F/1M/120V/STD BLX/4P (4 pack)	25	E26	120	Frost	1000	C-9	215	4.3 108	2.9 73	120
50921	25A19/SW/1M/120V/STD BLX/2P (2 pack)	25	E26	120	Soft white	1000	C-9	220	4.3 108	2.9 73	120
50114	40A19/CL/1M/120V/STD BLX/2P (2 pack)	40	E26	120	Clear	1000	C-9	455	4.3 108	2.9 73	120
50106	40A19/F/1M/120V/STD BLX/2P (2 pack)	40	E26	120	Frost	1000	C-9	455	4.3 108	2.9 73	120
50103	40A19/SW/1M/120V/STD BLX/2P (2 pack)	40	E26	120	Soft white	1000	C-9	440	4.3 108	2.9 73	120
50102	60A19/CL/1M/120V/STD BLX/2P (2 pack)	60	E26	120	Clear	1000	C-9	830	4.3 108	2.9 73	120
50107	60A19/F/1M/120V/STD BLX/2P (2 pack)	60	E26	120	Frost	1000	C-9	830	4.3 108	2.9 73	120
50104	60A19/SW/1M/120V/STD BLX/2P (2 pack)	60	E26	120	Soft white	1000	C-9	730	4.3 108	2.9 73	120
* 50115	100A19/CL/1M/120V/STD BLX/2P (2 pack)	100	E26	120	Clear	1000	C-9	1630	4.3 108	2.9 73	120
* 50108	100A19/F/1M/120V/STD BLX/2P (2 pack)	100	E26	120	Frost	1000	C-9	1630	4.3 108	2.9 73	120
* 50876	100A19/SW/1M/120V/STD BLX/2P (2 pack)	100	E26	120	Soft white	1000	C-9	1400	4.3 108	2.9 73	120
A21											
50516	50/150A21/WH/2M/120V/STD BLX	50 100 150	E26d	120	White	2000	CC8 CC8	270 780 1050	5.3 135	3.9 99	120
B10											
50522	25B10/CL/2M/E12/120V/STD BLX	25	E12	120	Clear	2000	CC-2V	220	3.9 99	1.9 47	500
50525	25B10/CL/2M/120V/STD BLX	25	E26	120	Clear	2000	CC-2V	220	3.9 99	2.1 54	500
50523	40B10/CL/2M/E12/120V/STD BLX	40	E12	120	Clear	2000	CC-2V	360	3.9 99	1.9 47	500
50526	40B10/CL/2M/120V/STD BLX	40	E26	120	Clear	2000	CC-2V	360	3.9 99	2.1 54	500

* Not for sale in British Columbia as per BC Energy Efficiency Act Standards on General Service Lighting.

Order code	Description	Watts (W)	Base	Volts (V)	Finish/ Colour	Average life (hrs)	Filament	Initial lumens (lm)	MOL (in.) (mm)		LCL (in.) (mm)		Case qty
B10 (Suitable for use base up)													
50524	60B10/CL/2M/E12/120V/STD BLX	60	E12	120	Clear	2000	C-7A/3	600	3.9	99	2.0	52	500
50527	60B10/CL/2M/120V/STD BLX	60	E26	120	Clear	2000	C-7A/3	600	3.9	99	2.1	54	500
BR30													
52002	65BR30/FL/2M/ES/120V/STD BLX	65	E26	120	Clear	2000	CC-6	530	5.1	130	3.3	84	60
BR40													
¹ 50224	75BR40/FL/2M/120V/STD BLX	75	E26	120	Clear	2000	CC-6	720	6.6	167	4.3	108	24
¹ 50478	100BR40/FL/2M/120V/STD BLX	100	E26	120	Clear	2000	CC-6	1050	6.6	167	4.3	108	24
¹ 52059	120BR40/FL/2M/ES/120V/STD BLX	120	E26	120	Clear	2000	C-9	1080	6.6	167	4.3	108	24
G16.5													
50685	25G16.5/CL/2M/E12/120V/STD BLX	25	E12	120	Clear	2000	CC-2V	220	3.0	76	1.9	47	500
10270	25G16.5/WH/2M/E12/120V/STD BLX	25	E12	120	White	2000	CC-2V	180	3.0	76	1.9	47	500
50686	40G16.5/CL/2M/E12/120V/STD BLX	40	E12	120	Clear	2000	CC-2V	370	3.0	76	1.9	47	500
50687	40G16.5/WH/2M/E12/120V/STD BLX	40	E12	120	White	2000	CC-2V	330	3.0	76	1.9	47	500
50688	60G16.5/CL/2M/E12/120V/STD BLX	60	E12	120	Clear	2000	CC-2V	650	3.0	76	1.9	47	500
50689	60G16.5/WH/2M/E12/120V/STD BLX	60	E12	120	White	2000	CC-2V	580	3.0	76	1.9	47	500
10159	60G16.5/WH/2M/120V/STD BLX	60	E26	120	White	2000	CC-2V	580	3.0	76	1.9	47	500
G25													
50167	25G25/CL/2M/120V/STD BLX	25	E26	120	Clear	2000	CC-6	220	4.5	114	3.0	76	150
50168	25G25/WH/2M/120V/STD BLX	25	E26	120	White	2000	CC-6	200	4.5	114	3.0	76	60
50169	40G25/CL/2M/120V/STD BLX	40	E26	120	Clear	2000	CC-6	440	4.5	114	3.0	76	150
50170	40G25/WH/2M/120V/STD BLX	40	E26	120	White	2000	CC-6	400	4.5	114	3.0	76	150
50171	60G25/CL/2M/120V/STD BLX	60	E26	120	Clear	2000	CC-6	750	4.5	114	3.0	76	150
50172	60G25/WH/2M/120V/STD BLX	60	E26	120	White	2000	CC-6	700	4.5	114	3.0	76	150
G30													
50180	40G30/CL/2M/120V/STD BLX	40	E26	120	Clear	2000	CC-6	440	5.4	137	3.3	84	100
50181	40G30/WH/2M/120V/STD BLX	40	E26	120	White	2000	CC-6	400	5.4	137	3.3	84	100
50182	60G30/CL/2M/120V/STD BLX	60	E26	120	Clear	2000	CC-6	750	5.4	137	3.3	84	100
50183	60G30/WH/2M/120V/STD BLX	60	E26	120	White	2000	CC-6	700	5.4	137	3.3	84	100
G40													
50173	40G40/CL/2M/120V/STD BLX	40	E26	120	Clear	2000	CC-6	440	6.9	176	3.9	99	24
50175	60G40/CL/2M/120V/STD BLX	60	E26	120	Clear	2000	CC-6	520	6.9	176	3.9	99	24
50177	100G40/CL/2M/120V/STD BLX	100	E26	120	Clear	2000	CC-6	1350	6.9	176	3.9	99	24
50178	100G40/WH/2M/120V/STD BLX	100	E26	120	White	2000	CC-6	1200	6.9	176	3.9	99	24
50179	150G40/WH/2M/120V/STD BLX	150	E26	120	White	2000	CC-6	1650	6.9	176	3.9	99	24
R20													
51080	30R20/FL/2M/120V/STD BLX	30	E26	120	Frost	2000	CC-6	170	3.9	99	3.0	76	200
61706	45R20/FL/2M/120V/STD BLX	45	E26	120	Frost	2000	CC-6	380	3.9	100	3.0	75	60
¹ 51079	50R20/FL/2M/120V/STD BLX	50	E26	120	Frost	2000	C-9/5	320	3.9	99	3.0	76	200
¹ 51081	75R20/FL/2M/120V/STD BLX	75	E26	120	Clear	2000	C-9/5	650	3.9	99	3.0	76	200
S11													
52167	40S11/CL/1M/E17/120V/STD BLX	40	E17	120	Clear	1000	C-7A	400	2.3	59	1.6	41	500

¹This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.