


T&B Conduit Fittings


Rigid and Intermediate Metal Conduit Fittings



For reducing the threaded opening in conduit bodies or any female threaded fitting. Smooth, built-in bushing completely covers rough ends of conduit. Iron or steel construction. Steel from 600-TB thru 606-TB, also 614 & 615.

Threaded Reducers

Stl. or M.I.	Cat. No.		Size	Dimensions (in.)
	Alum.			A
600-TB	600AL-TB		1/2" to 3/8"	5/8
601-TB	601AL-TB		3/4" to 1/2"	19/32
602-TB	602AL-TB		1" to 1/2"	19/32
603-TB	603AL-TB		1" to 3/4"	19/32
604-TB	604AL-TB		1-1/4" to 1/2"	19/32
605-TB	605AL		1-1/4" to 3/4"	19/32
606-TB	606AL		1-1/4" to 1"	11/16
607	607AL		1-1/2" to 1/2"	15/16
608	608AL		1-1/2" to 3/4"	15/16
609	609AL		1-1/2" to 1"	1-3/32
610	610AL		1-1/2" to 1-1/4"	27/32
611-TB	611AL		2" to 1/2"	23/32
612	612AL		2" to 3/4"	1-1/16
613	613AL		2" to 1"	1-1/16
614-TB	614AL		2" to 1-1/4"	1-1/16
615-TB	615AL		2" to 1-1/2"	27/32



Washers reduce knockout hole in outlet box. Newly designed of galvanized steel. These washers, used in pairs, interlock and form a rib which centers the washers and conduit in the knockout.

Reducing Washers



Cat. No.	Size	Dimensions (in.)	
		A	B
3700	3/4" to 3/8"	1-3/8	45/64
3701	3/4" to 1/2"	1-3/8	7/8
3702	1" to 3/8"	1-5/8	45/64
3703	1" to 1/2"	1-5/8	7/8
3704	1" to 3/4"	1-5/8	1-3/32
3705-TB	1-1/4" to 3/8"	2	45/64
3706	1-1/4" to 1/2"	2	7/8
3707	1-1/4" to 3/4"	2	1-3/32
3708	1-1/4" to 1"	2	1-23/64
3709	1-1/2" to 3/8"	2-1/4	45/64
3710	1-1/2" to 1/2"	2-1/4	7/8
3711	1-1/2" to 3/4"	2-1/4	1-3/32
3712	1-1/2" to 1"	2-1/4	1-23/64
3713	1-1/2" to 1-1/4"	2-1/4	1-23/32
3714	2" to 1/2"	2-3/4	7/8
3715-TB	2" to 3/4"	2-3/4	1-3/32
3716	2" to 1"	2-3/4	1-23/64
3717	2" to 1-1/4"	2-3/4	1-23/32
3718	2" to 1-1/2"	2-3/4	1-31/32