



# **E.B. Horsman & Son**

*The Electrical Distributor of Choice!*

*proud distributor  
of*



Hammond Power  
Solutions Inc.

Visit our

**You Tube** Channel

[www.youtube.com/user/ebhorsman](http://www.youtube.com/user/ebhorsman)

Shop Online



[ebhorsman.com](http://ebhorsman.com)

## SINGLE PHASE, NEMA 3R STYLE ENCLOSURE



347/380 Primary Volts  120/240 Secondary Volts

50/60 Hz

| kVA  | Catalog Number | Case Style<br>(Pages 266 - 268) | Approx. Dimensions<br>(Inches) |       |        | Approx. Weight<br>(Lbs.) | Mtg Type<br>W - Wall<br>F - Floor | Wiring<br>Diagram<br>(Pages 281 - 293) |
|------|----------------|---------------------------------|--------------------------------|-------|--------|--------------------------|-----------------------------------|----------------------------------------|
|      |                |                                 | Width                          | Depth | Height |                          |                                   |                                        |
| 0.05 | C1FC05JE       | NQ0                             | 3.75                           | 5.25  | 7.25   | 7                        | W                                 | SCD33                                  |
| 0.10 | C1FC10JE       | NQ0                             | 3.75                           | 5.25  | 7.25   | 7                        | W                                 | SCD33                                  |
| 0.15 | C1FC15JE       | NQ0                             | 3.75                           | 5.25  | 7.25   | 8                        | W                                 | SCD33                                  |
| 0.25 | C1FC25JE       | NQ0                             | 3.75                           | 5.25  | 7.25   | 9                        | W                                 | SCD33                                  |
| 0.35 | C1FC35JE       | NQ1                             | 4.50                           | 5.75  | 7.25   | 14                       | W                                 | SCD33                                  |
| 0.50 | C1FC50JE       | NQ1                             | 4.50                           | 5.75  | 7.25   | 14                       | W                                 | SCD33                                  |
| 0.75 | C1FC75JES      | NQ2                             | 5.00                           | 4.75  | 9.25   | 23                       | W                                 | SCD33                                  |
| 1    | C1F1C0JES      | NQ3                             | 5.88                           | 5.50  | 10.50  | 32                       | W                                 | SCD33                                  |
| 1.5  | C1F1C5JES      | NQ3                             | 5.88                           | 5.50  | 10.50  | 35                       | W                                 | SCD33                                  |
| 2    | C1F002JES      | NQ4                             | 7.00                           | 6.50  | 11.75  | 51                       | W                                 | SCD33                                  |
| 3    | C1F003JES      | NQ5                             | 10.00                          | 7.75  | 17.25  | 98                       | W                                 | SCD33                                  |
| 5    | C1F005JES      | NQ5                             | 10.00                          | 7.75  | 17.25  | 120                      | W                                 | SCD44                                  |
| 7.5  | C1F007JES      | NQ6A                            | 12.25                          | 9.25  | 17.63  | 162                      | W                                 | SCD44                                  |
| 10   | C1F010JES      | NQ6                             | 12.25                          | 9.25  | 20.88  | 194                      | W                                 | SCD44                                  |

600 Primary Volts 120/240 Secondary Volts

60 Hz

| kVA  | Catalog Number | Case Style<br>(Pages 266 - 268) | Approx. Dimensions<br>(Inches) |       |        | Approx. Weight<br>(Lbs.) | Mtg Type<br>W - Wall<br>F - Floor | Wiring<br>Diagram<br>(Pages 281 - 293) |
|------|----------------|---------------------------------|--------------------------------|-------|--------|--------------------------|-----------------------------------|----------------------------------------|
|      |                |                                 | Width                          | Depth | Height |                          |                                   |                                        |
| 0.05 | C1FC05PE       | NQ0                             | 3.75                           | 5.25  | 7.25   | 7                        | W                                 | SCD4                                   |
| 0.10 | C1FC10PE       | NQ0                             | 3.75                           | 5.25  | 7.25   | 7                        | W                                 | SCD4                                   |
| 0.15 | C1FC15PE       | NQ0                             | 3.75                           | 5.25  | 7.25   | 8                        | W                                 | SCD4                                   |
| 0.25 | C1FC25PE       | NQ0                             | 3.75                           | 5.25  | 7.25   | 9                        | W                                 | SCD4                                   |
| 0.35 | C1FC35PE       | NQ1                             | 4.50                           | 5.75  | 7.25   | 15                       | W                                 | SCD4                                   |
| 0.50 | C1FC50PE       | NQ1                             | 4.50                           | 5.75  | 7.25   | 16                       | W                                 | SCD4                                   |
| 0.75 | C1FC75PES      | NQ2                             | 5.00                           | 4.75  | 9.25   | 23                       | W                                 | SCD4                                   |
| 1    | C1F1C0PES      | NQ3                             | 5.88                           | 5.50  | 10.50  | 24                       | W                                 | SCD4                                   |
| 1.5  | C1F1C5PES      | NQ3                             | 5.88                           | 5.50  | 10.50  | 33                       | W                                 | SCD4                                   |
| 2    | C1F002PES      | NQ4                             | 7.00                           | 6.50  | 11.75  | 42                       | W                                 | SCD4                                   |
| 3    | C1F003PES      | NQ4                             | 7.00                           | 6.50  | 11.75  | 55                       | W                                 | SCD4                                   |
| 5    | C1F005PES      | NQ5                             | 10.00                          | 7.75  | 17.25  | 120                      | W                                 | SCD4                                   |
| 7.5  | C1F007PES      | NQ6A                            | 12.25                          | 9.25  | 17.63  | 148                      | W                                 | SCD5                                   |
| 10   | C1F010PES      | NQ6                             | 12.25                          | 9.25  | 20.88  | 179                      | W                                 | SCD5                                   |
| 15   | C1F015PES      | NQ7                             | 14.50                          | 10.75 | 21.38  | 265                      | W                                 | SCD5                                   |
| 25   | C1F025PES      | NQ8                             | 14.50                          | 10.75 | 27.38  | 385                      | W                                 | SCD5                                   |
| 37.5 | C1F037PES      | NQS10                           | 21.88                          | 18.50 | 31.00  | 598                      | F or W*                           | SCD5                                   |

\*OPTIONAL WALL MOUNTING KIT REQUIRED.  
REFER TO PAGE 278 FOR DETAILS.

## Export Model



190/200/208/220/240<sup>1</sup> X 380/400/416/440/480<sup>1</sup> Primary Volts 120/240 Secondary Volts 50/60 Hz

| kVA  | Catalog Number | Case Style<br>(Pages 266 - 268) | Approx. Dimensions<br>(Inches) |       |        | Approx. Weight<br>(Lbs.) | Mtg Type<br>W - Wall<br>F - Floor | Wiring<br>Diagram<br>(Pages 281 - 293) |
|------|----------------|---------------------------------|--------------------------------|-------|--------|--------------------------|-----------------------------------|----------------------------------------|
|      |                |                                 | Width                          | Depth | Height |                          |                                   |                                        |
| 0.05 | C1FC05XE       | NQ0                             | 3.75                           | 5.25  | 7.25   | 7                        | W                                 | SCD28                                  |
| 0.10 | C1FC10XE       | NQ0                             | 3.75                           | 5.25  | 7.25   | 7                        | W                                 | SCD28                                  |
| 0.15 | C1FC15XE       | NQ0                             | 3.75                           | 5.25  | 7.25   | 9                        | W                                 | SCD28                                  |
| 0.25 | C1FC25XE       | NQ0                             | 3.75                           | 5.25  | 7.25   | 10                       | W                                 | SCD28                                  |
| 0.35 | C1FC35XE       | NQ1                             | 4.50                           | 5.75  | 7.25   | 15                       | W                                 | SCD28                                  |
| 0.50 | C1FC50XE       | NQ1                             | 4.50                           | 5.75  | 7.25   | 16                       | W                                 | SCD28                                  |
| 0.75 | C1FC75XES      | NQ2                             | 5.00                           | 4.75  | 9.25   | 24                       | W                                 | SCD28                                  |
| 1    | C1F1C0XES      | NQ3                             | 5.88                           | 5.50  | 10.50  | 32                       | W                                 | SCD28                                  |
| 1.5  | C1F1C5XES      | NQ4                             | 7.00                           | 6.50  | 11.75  | 37                       | W                                 | SCD28                                  |
| 2    | C1F002XES      | NQ4                             | 7.00                           | 6.50  | 11.75  | 52                       | W                                 | SCD28                                  |
| 3    | C1F003XES      | NQ5                             | 10.00                          | 7.75  | 17.25  | 97                       | W                                 | SCD2                                   |
| 5    | C1F005XES      | NQ5                             | 10.00                          | 7.75  | 17.25  | 120                      | W                                 | SCD2                                   |
| 7.5  | C1F007XES      | NQ6A                            | 12.25                          | 9.25  | 17.63  | 148                      | W                                 | SCD2                                   |
| 10   | C1F010XES      | NQ6                             | 12.25                          | 9.25  | 20.88  | 179                      | W                                 | SCD2                                   |

Note <sup>1</sup>: The primary voltage ratio of 240 or 480 is available at 60Hz only with a secondary voltage of approximately 130/262V.



## Lower Mainland Locations

Burnaby  
3935 2nd Avenue  
Burnaby, BC V5C 3W9  
Tel: 604-292-4800

Langley  
#101 - 20550 Duncan Way  
Langley, BC V3A 7A3  
Tel: 604-533-1275

Richmond  
12360 Vickers Way  
Richmond, BC V6V 1H9  
Tel: 604-273-1981

Surrey  
13055 80th Avenue  
Surrey, BC V3W 3B1  
Tel: 604-596-7111

## Island Locations

Campbell River  
1030 B - 9th Avenue  
Campbell River, BC V9W 4C2  
Tel: 250-287-9265

Courtenay  
2615 Moray Place  
Courtenay, BC V9N 8A9  
Tel: 250-334-0338

Duncan  
5286 Polkey Road  
Duncan, BC V9L 6W3  
Tel: 250-748-3377

Parksville  
#105 - 425 E. Stanford Avenue  
Parksville, BC V9P 2N4  
Tel: 250-954-1797

## Interior Locations

Cranbrook  
Unit A #800 Industrial Road. #2  
Cranbrook, BC V1C 4C9  
Tel: 250-489-4591

Kamloops  
B-983 Camosun Crescent  
Kamloops, BC V2C 6G1  
Tel: 250-374-3191

Penticton  
401 Okanagan Avenue  
Penticton, BC V2A 3K1  
Tel: 250-492-4032

Vernon  
5203 24th Street  
Vernon, BC V1T 8X7  
Tel: 250-545-2191

Williams Lake  
527 S. MacKenzie Avenue  
Williams Lake, BC V2G 1C8  
Tel: 250-392-7795

## Alberta Locations

Unit 9, 7223 68 Avenue,  
Edmonton, Alberta T6B 3T6

## Northern Locations

Dawson Creek  
1101 97th Avenue  
Dawson Creek, BC V1G 1N5  
Tel: 250-782-4896

Fort Nelson  
PO Box 3266 - 5016 48th Avenue  
Fort Nelson, BC V0C 1R0  
Tel: 250-233-8570

Kitimat  
622 Commercial Avenue  
Kitimat, BC V8C 2C5  
Tel: 250-632-3774

Prince George  
2255 S. Quinn Street  
Prince George, BC V2N 2X4  
Tel: 250-563-0575

Terrace  
5000 Pohle Avenue  
Terrace, BC V8G 4S8  
Tel: 250-635-6379

## Specialty Divisions

Process, Automation &  
Controls Group  
Tel: 778-545-9916

Projects Group  
Tel: 604-596-7111

Data Communications Group  
Tel: 778-545-9916

Lighting Specialist  
Tel: 778-545-9916



Visit our

**You Tube** Channel

[www.youtube.com/user/ebhorsman](http://www.youtube.com/user/ebhorsman)

Head Office  
19295 25th Avenue  
Surrey, BC V3Z 3X1  
Tel: 778-545-9916  
Fax: 778-545-3099

Toll Free: 1-888-467-7626

Shop Online



[ebhorsman.com](http://ebhorsman.com)