

### Product type designation

**Split Connect Terminator (non-Ex)**  
PROFIBUS PA SPLITCONNECT TERMINATOR, FOR  
TERMINATING OF PROFIBUS PA SEGMENTS, NOT SUITABLE  
FOR APPLICATION IN EX-AREA, PACK. UNIT: 5 PIECES PER  
PACK



### Electrical data

Transfer rate / with PROFIBUS PA	31.25 kbit/s
----------------------------------	--------------

### Permitted ambient conditions

Ambient temperature / during operation	-40 ... +85 °C
Ambient temperature / during storage	-40 ... +85 °C
Ambient temperature / during transport	-40 ... +85 °C
Protection class IP	IP67

### Further Information / Internet Links

#### Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL <http://www.siemens.com/snst>
- to website: Industrial communication <http://www.siemens.com/simatic-net>
- to website: Industry Mall <https://mall.industry.siemens.com>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx Download Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

last modified:

24.09.2015