

T&B Conduit Fittings

Flexible Cord and Cable Fittings



Strain Relief Fittings



Swing Radius
90° with neoprene bushings, tapered hub threads, malleable iron.

Cat. No.	Cable Size min.-max.	Hub Size	Dimensions (in.)			Throat Dia.
			A	B	C	
2267	(.125-.250)	1/2"	1-5/32	1-23/32	5/8	19/32
2268	(.250-.375)	1/2"	1-5/32	1-23/32	5/8	19/32
2269	(.375-.500)	1/2"	1-5/32	1-23/32	5/8	19/32
2270	(.450-.560)	1/2"	1-5/32	1-23/32	5/8	19/32
2250*	(.500-.625)	1/2"	1-3/8	1-11/16	9/16	39/64
2251*	(.625-.750)	1/2"	1-3/8	1-11/16	9/16	39/64
2252	(.125-.250)	3/4"	1-3/8	1-3/4	41/64	25/32
2271	(.250-.375)	3/4"	1-3/8	1-5/8	41/64	25/32
2272	(.375-.500)	3/4"	1-3/8	1-5/8	41/64	25/32
2273	(.500-.625)	3/4"	1-3/8	1-5/8	41/64	25/32
2274*	(.620-.750)	3/4"	1-3/8	1-5/8	41/64	25/32
2253*	(.750-.880)	3/4"	1-11/16	1-31/32	9/16	25/32
2254	(.375-.500)	1"	1-3/8	2	13/16	1
2255	(.500-.625)	1"	1-3/8	2	13/16	1
2256*	(.625-.750)	1"	1-3/8	2	13/16	1
2275	(.750-.875)	1"	1-11/16	2	13/16	1
2276	(.875-.985)	1"	1-11/16	2	13/16	1
2257*	(.880-1.065)	1"	2-3/32	2-21/32	25/32	15/16
2258*	(1.065-1.205)	1"	2-3/32	2-21/32	25/32	15/16
2277	(.880-1.065)	1-1/4"	2-3/32	2-7/8	27/32	1-5/16
2278	(1.065-1.205)	1-1/4"	2-3/32	2-7/8	27/32	1-5/16
2279*	(1.187-1.375)	1-1/4"	2-11/32	2-13/16	13/16	1-11/32
2280*	(1.375-1.485)	1-1/4"	2-11/32	2-13/16	13/16	1-11/32
2281	(.812-1.000)	1-1/2"	2-11/32	2-7/8	13/16	1-15/32
2282	(1.000-1.187)	1-1/2"	2-11/32	2-7/8	13/16	1-15/32
2283*	(1.187-1.375)	1-1/2"	2-11/32	2-7/8	13/16	1-15/32
2284	(1.125-1.375)	2"	2-13/16	3-1/4	27/32	1-31/32
2285	(1.375-1.625)	2"	2-13/16	3-1/4	27/32	1-31/32
2286	(1.625-1.875)	2"	2-13/16	3-1/4	27/32	1-31/32

* Remove sufficient outer covering of cable to permit conductors to pass through fitting body.

Complies with J.I.C. standards and Federal Specs W-F-406B, W-F-408B.

Meets Coast Guard CG293

For Wiremesh Grips refer to page 78.