


T&B Conduit Fittings

Armoured Cable and Flexible Metal Conduit Fittings



Tite-Bite® Fittings—Nylon Insulated



Steel or malleable iron.

The tough lining of insulation and the Tite-Bite principles make these fittings a "must" when conductors are subject to conditions of vibration or strain.

Cat. No.	Cable Opening (in.)		Trade Size	K.O. Size	Dimensions (in.)		
	max.	min.			A	B	C
3110-C*	.656	.437	3/8"	1/2"	1-7/16	1-5/16	7/16
3112	.937	.750	1/2"	1/2"	1-25/32	1-3/4	1-9/32
3115*	1.125	.906	3/4"	3/4"	2	1-3/4	1-9/32
3117*	1.468	1.250	1"	1"	2-3/8	1-3/4	1-7/32
3118†	1.750	1.562	1-1/4"	1-1/4"	2-3/4	2	1-11/32
3119†	2.031	1.812	1-1/2"	1-1/2"	3-1/8	2-5/8	1-7/8
3120†	2.500	2.312	2"	2"	3-3/4	2-3/4	1-15/16
3121†	3.062	2.812	2-1/2"	2-1/2"	4-3/8	3-1/4	2-3/8
3122†	3.562	3.312	3"	3"	5	3-1/4	2-3/8
3123‡	4.060	3.620	3-1/2"	3-1/2"	5-1/4	3-11/16	2-15/32
3124**†	4.560	4.120	4"	4"	5-3/4	3-25/32	2-1/2
3125**	5.500	4.600	5"	5"	6-7/8	4-27/32	3

Material: Steel thru 3/4" trade size.

* U.L. Listed for armoured cable only.


† U.L. Listed for flexible metal conduit only.

‡ CSA not applicable.

** Not U.L. Listed or CSA Certified.



Tite-Bite® Fittings



Steel or malleable iron.

Easy to install with double grip saddle. These fittings are completely salvageable. The 2/3" and 1/2" sizes are made of formed steel which produce a uniform high quality and a smooth throat that protects conductor insulation. 3/4" and larger size are malleable iron.

Cat. No.	Cable Opening (in.)		Trade Size	K.O. Size	Dimensions (in.)		
	max.	min.			A	B	C
300-TBC*	.656	.437	3/8"	1/2"	7/16	1-5/16	7/16
302-C	.937	.750	1/2"	1/2"	1-7/64	1-11/16	3/4
304	1.093	.906	3/4"	3/4"	1-7/32	1-11/16	29/32
306	1.468	1.250	1"	1"	1-1/8	1-3/4	1-1/4
308†	1.750	1.562	1-1/4"	1-1/4"	1-1/4	2-1/32	1-9/16
310†	2.031	1.812	1-1/2"	1-1/2"	1-3/4	2-9/16	1-13/16
312†	2.500	2.312	2"	2"	1-13/16	2-13/16	2-5/16
314†	3.062	2.812	2-1/2"	2-1/2"	2-1/4	3-1/8	2-13/16
316†	3.562	3.312	3"	3"	2-1/4	3-3/16	3-5/16

Material: Steel thru 3/4" trade size.

* U.L. Listed for armoured cable only.

† U.L. Listed for flexible metal conduit only.