


# T&B Conduit Fittings

## Rigid and Intermediate Metal Conduit Fittings



*Nylon insulated.*

Aluminum, steel, or malleable iron (steel through 1"). With Neoprene "O" Ring provides a watertight threaded hub on enclosures. U.L. Listed 105°C.



### Steel/Malleable Iron and Aluminum Hub Fittings\*†



| Stl. or M.I. | Cat. No. | Alum.** | Size  | Dimensions (in.) |         |         | Wall Thk. (max.)in. |
|--------------|----------|---------|-------|------------------|---------|---------|---------------------|
|              |          |         |       | A                | B       | C       |                     |
| 370          | 370AL    |         | 1/2   | 1-3/8            | 1-5/16  | 3/4     | 5/16                |
| 371          | 371AL    |         | 3/4   | 1-5/8            | 1-3/8   | 7/8     | 5/16                |
| 372          | 372AL    |         | 1     | 2-3/32           | 1-23/32 | 1-7/32  | 5/16                |
| 373          | 373AL    |         | 1-1/4 | 2-9/16           | 2       | 1-11/32 | 5/16                |
| 374          | 374AL    |         | 1-1/2 | 3-3/32           | 2       | 1-11/32 | 5/16                |
| 375          | 375AL    |         | 2     | 3-5/8            | 1-31/32 | 1-11/32 | 5/16                |
| 376          | —        |         | 2-1/2 | 4-1/8            | 2-21/32 | 1-15/16 | 5/16                |
| 377          | —        |         | 3     | 5                | 2-31/32 | 2       | 1/2                 |
| 378          | —        |         | 3-1/2 | 5-9/16           | 3-1/8   | 2-1/8   | 1/2                 |
| 379-TB       | —        |         | 4     | 6-9/16           | 3-1/8   | 2-1/8   | 1/2                 |
| 381-TB       | —        |         | 5     | 8                | 4       | 2-3/16  | 1/2                 |
| 382-TB       | —        |         | 6     | 9-3/16           | 4       | 2-3/16  | 1/2                 |

\* General purpose equipment is specifically permitted per CEC 18-050.

\*\* Aluminum not available with insulated throat.

† U.L. Listed raintight and CSA Certified watertight and dust tight.

For Dura-Plate™ finish, add prefix 040- to Cat. No. Consult Customer Service for details.

### Bullet® Hub Fittings with Bonding Locknut — Nylon Insulated



| Cat. No. | Size (in.) | Description                               |
|----------|------------|-------------------------------------------|
| 401      | 1/2        |                                           |
| 402      | 3/4        |                                           |
| 403-TB   | 1          | Available in steel or malleable iron      |
| 404-TB   | 1-1/4      | (steel through 1 inch.).                  |
| 405-TB   | 1-1/2      | Used with a neoprene "O" ring to provide  |
| 406-TB   | 2          | a watertight* threaded hub on enclosures. |
| 407      | 2-1/2      | Supplied with 106 series bonding nut.     |
| 408      | 3          | Temperature rating: 105°C.                |
| 409      | 3-1/2      |                                           |
| 410-TB   | 4          |                                           |

CSA certified watertight and dust tight.