SSFR

SELF-REGULATING FREEZE PROTECTION CABLE REEL

2 YEAR WARRANTY

MELT AWAY YOUR WORRIES

SSFR heating cable increases or decreases the heat output in a self-regulating way depending on changes in the ambient temperature, so a thermostat may not be necessary in some applications. It will never overheat or burn out even when overlapped. This heating cable reel is available with optional termination, power connection, splice and tee kits to reduce installation time and require no special tools.

ENERGY EFFICIENT
AUTOMATICALLY VARIES ITS POWER OUTPUT IN RESPONSE TO TEMPERATURE CHANGES

EASY TO INSTALL
CAN BE CUT TO ANY LENGTH (UP TO MAXIMUM CIRCUIT LENGTH) REQUIRED ON SITE WITH NO WASTED CABLE

SAFE
EVEN WHEN OVERLAPPED

POWER CONNECTION, SPLICE, TEE AND END SEAL KIT
REDUCES INSTALLATION TIME

MANUFACTURING

- normal cable width 0.42 in. (10.6 mm)
- normal cable thickness 0.23 in. (5.8 mm)
- cable bus wire gauge 16 AWG

WATTAGE

- 5 W/ft, 8 W/ft, 10 W/ft

INSTALLATION

- maximum exposure temperature is 85 °C (185 °F)
- Minimum installation temperature -40 °C (-40 °F)

WARRANTY

- two years

IDEAL FOR:

pipes at risk of freezing and roofs and gutters with ice damming problems

°STELPRO

°STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. **No returns accepted on optional-colour products.**
For all the latest models and prices, please refer to our website at www.stelpro.com.

FC_SSFR_EN_080519

TECHNICAL SPECIFICATIONS

PRODUCT	LENGTH	POWER OUTPUT	PRICE
CODE	FT	WATTS	
120 VOLTS			
SSFR1W05L1000	1000	5	**5556.00**
SSFR1W08L1000	1000	8	**5556.00**
SSFR1W05L0500	500	5	**2940.00**
SSFR1W08L0500	500	8	**2940.00**
240 VOLTS			
SSFR2W05L1000	1000	5	**5556.00**
SSFR2W08L1000	1000	8	**5556.00**
SSFR2W10L1000	1000	10	**5556.00**
SSFR2W05L0500	500	5	**2940.00**
SSFR2W08L0500	500	8	**2940.00**
SSFR2W10L0500	500	10	**2940.00**

POWER OUTPUT CURVES

Nominal power output at nominal voltage (120 V or 240 V) when SSFR heating cable installed on insulated metal pipes.



ADJUSTMENT FACTORS

POWER	POWER OUTPUT		CIRCUIT LENGTH	
W/FT	208 V	277 V	208 V	277 V
5	0.85	1.12	0.94	1.09
8	0.89	1.08	0.93	1.11
10	0.89	1.08	0.92	1.11

°STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. **No returns accepted on optional-colour products.**
For all the latest models and prices, please refer to our website at www.stelpro.com.

MAXIMUM CIRCUIT LENGTH PER CIRCUIT BREAKER

POWER	AMBIENT TEMPERATURE AT START-UP		120 V				240 V			
			15 A	20 A	30 A	40 A	15 A	20 A	30 A	40 A
W/FT	°F	°C	FT				FT			
5	50	10	230	270	270	270	460	540	540	540
	32	0	230	270	270	270	460	540	540	540
	14	-10	180	210	270	270	360	420	540	540
	0	-18	140	190	270	270	285	380	540	540
	-20	-29	125	165	250	270	250	330	500	540
	-40	-40	110	145	220	270	220	295	420	540
8	50	10	150	200	210	210	300	400	420	420
	32	0	150	200	210	210	300	400	420	420
	14	-10	140	150	205	210	280	300	410	420
	0	-18	100	130	200	210	200	265	400	420
	-20	-29	85	115	175	210	175	235	350	420
	-40	-40	80	105	155	210	155	210	315	420
10	50	10	120	160	180	180	240	315	360	360
	32	0	105	140	170	180	210	280	340	360
	14	-10	95	125	165	180	190	250	330	360
	0	-18	80	110	160	180	160	215	325	360
	-20	-29	70	95	140	180	145	190	285	360
	-40	-40	60	85	125	170	125	170	255	340

ACCESSORIES

PRODUCT	DESCRIPTION	PRICE
SSFR-ALUTAPE	aluminum adhesive foil tape	**30.00**
SSFR-FIBTAPE	fiberglass adhesive tape	**40.00**
SSFR00	power connection kit for SSFR cable	**65.00**
SSFR03	fiberglass adhesive tape and warning labels	**45.00**
SSFR08	plug-in power connection with GFCI kit for SSFR cable	**90.00**
SSFR10	splice and tee kit for SSFR cable	**45.00**
SSFR12	end seal kit for SSFR cable	**26.00**
SSFR13	roof clips for SSFP/SSFR cables (Kit of 10)	**33.00**
SSFR14	roof clips for SSFP/SSFR cables (Kit of 50)	**120.00**
SSFR15	downspout cable hanger bracket for SSFP/SSFR cables	**19.00**
SSFR-ENDSEAL	commercial end seal kit for SSFR cable	**30.00**
SSFR-SPLICE	commercial splice connection kit for SSFR cable	**80.00**
SSFR-TEE	commercial tee connection kit for SSFR cable	**80.00**
SSFR-JBOX	commercial junction box for SSFR cable	**270.00**
FPT130	electronic controller NEMA 4, 30 A @ 100V - 277 V with GFI 30 mA, setpoint selection -1 °C, 3 °C, 7 °C ou 10 °C (30 °F, 38 °F, 45 °F or 50 °F) awith 20 ft (6 m) sensor	**1395.00**
TPR-L1N-3X-Q10	thermostat NEMA 4, 22 A resistive @ 125 V/250 V/480 V,fixed setpoint at 4 °C (40 °F) with 3 ft (0.9 m) tin platted copper capillary	**340.00**
TRF115-005	thermostat NEMA 4, 25 A resistive @ 120 V/208 V/240 V/277 V, -18 °C to 49 °C (0 °F to 120 °F) with 5 ft (1.5 m) stainless steel capillary	**120.00**
GFPRO	electronic controller NEMA 4, 30 A @ 100 V - 277 V resistive with GFI 30 mA, 2 sensor inputs for GIT-1 sensor	**1395.00**
PDPRO	electronic controller NEMA 4, 30 A @ 100 V - 277 V resistive, 2 sensor inputs for GIT-1 sensor	**1195.00**
GIT-1	roof and gutter temperature and moisture sensor for GFPRO and PDPRO, stepoint at 3 °C (38 °F)	**725.00**
DS-8C	controller with aerial temperature and moisture deported 10 ft (3 m) sensor, 30 A @ 100 - 277 V	**550.00**
DS-9C	controller with aerial temperature and moisture deported 10 ft (3 m) sensor, 2 circuits of 30 A @ 100 - 277 V	**600.00**

°STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. **No returns accepted on optional-colour products.**
For all the latest models and prices, please refer to our website at www.stelpro.com.

TECHNICAL DRAWINGS





*STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. **No returns accepted on optional-colour products.**
For all the latest models and prices, please refer to our website at www.stelpro.com.